



SLIN GEARS- SUGGESTED MOTOR SHAFT LENGTHS			
SLIN GEAR	SHAFT TYPE	MIN. (IN.)	MAX. (IN.)
16B	7/8" 13T SPLINE	1.40	1.75
16C	1" 15T SPLINE	1.70	1.95
16D	1" ST. KEYED	1.80	2.10
16E	C/L 2000 BEARINGLESS	N/A	N/A
16F	C/L 4000 BEARINGLESS	N/A	N/A
16H	1 1/4" ST. KEYED	2.05	2.40
16I	1 1/4" 14T SPLINE	2.00	2.32
16M	1" SAE 6B SPLINE	1.95	2.30

THIS DRAWING CONTAINS PROPRIETARY AND CONFIDENTIAL INFORMATION OF HECO GEAR, INC. IN ACCEPTING THIS DRAWING, (CUSTOMER) ACKNOWLEDGES THE VALUE OF THE INTELLECTUAL PROPERTY CONTAINED HEREIN AND AGREES THAT THE INFORMATION IN THIS DRAWING IS THE PROPERTY OF AND PROPRIETARY TO HECO GEAR, INC. AND MAY NOT BE REPRODUCED WITHOUT THE EXPRESS WRITTEN PERMISSION OF HECO GEAR, INC. ALL RIGHTS RESERVED.



2300 DEL MARNE STREET
WEST SACRAMENTO, CA 95834
(916)-372-5411 FAX (916)-373-8822

TITLE			
MODEL 16 ASSEMBLY			
DESCRIPTION			
HECO 16 MODEL CODE: 16FF8 65			
SIZE	DRAWN BY:	ENG NO.	REV
D	KSC		-
SCALE: (DO NOT SCALE)		DATE: 04/19/01	SHEET 1 OF 1

REV			
DESCRIPTION	REVISIONS	DATE	APPROVED
-	-	-	-
-	-	-	-
-	-	-	-

©COPYRIGHT 2004, HECO GEAR, INC.