


1.502/1.498 TAPER PER FOOT
SAE TAPERED SHAFT J501
Ø.25 EXCEPT
1.5-12 UNF THREAD

SUN GEARS- SUGGESTED MOTOR SHAFT LENGTHS			
SUN GEAR	SHAFT TYPE	MIN. (IN.)	MAX. (IN.)
16B	7/8" 13T SPLINE	1.40	1.75
16C	1" 15T SPLINE	1.70	1.95
16D	1" ST. KEYED	1.80	2.10
16E	C/L 2000 BEARINGLESS	N/A	N/A
16F	C/L 4000 BEARINGLESS	N/A	N/A
16H	1 1/4" ST. KEYED	2.05	2.40
16I	1 1/4" 14T SPLINE	2.00	2.32
16M	1" SAE 6B SPLINE	1.95	2.30

THIS DRAWING CONTAINS PROPRIETARY AND CONFIDENTIAL INFORMATION OF HECO GEAR, INC. IN ACCEPTING THIS DRAWING, (CUSTOMER) ACKNOWLEDGES THE VALUE OF THE INTELLECTUAL PROPERTY CONTAINED HEREIN AND AGREES THAT THE INFORMATION IN THIS DRAWING IS THE PROPERTY OF AND PROPRIETARY TO HECO GEAR, INC. AND MAY NOT BE REPRODUCED WITHOUT THE EXPRESS WRITTEN PERMISSION OF HECO GEAR, INC. ALL RIGHTS RESERVED.

©COPYRIGHT 2004, HECO GEAR, INC.

REV	DESCRIPTION	DATE	APPROVED
-	-	--	--
-	-	--	--
-	-	--	--


HECO GEAR
 2300 DEL MONTE STREET
 WEST SACRAMENTO, CA 95601
 (916) 372-2411 FAX (916) 373-0082

TITLE	MODEL 16 ASSEMBLY
DESCRIPTION	HECO 16 MODEL CODE: 16CF355
SIZE	D
DRAWN BY:	KSC
ENG NO.	-----
SCALE:	10:1 NOT SCALE
DATE:	04/19/01
SHEET	1 OF 1