



Spline Data

NO. TEETH	20		
PITCH	6/12		
PITCH DIA.	3.3333	⊙ A	.002
PRESSURE ANGLE	30°		
TOOTH THKNS	MAX. EFF.	.2602 (6.609)	
	MAX. ACT.	.2583 (6.561)	
	MIN. ACT.	.2569 (6.525)	
PIN DIA.	.3200 (8.1280)		
MEAS. OVER 2 PINS, MAX.	3.8222 (97.084)		
	MIN.	3.8201 (97.031)	
TIF DIA. MAX.	3.1600 (80.264)		
MINOR DIA.	MAX.	3.1293 (79.484)	
	MIN.	3.1073 (78.925)	
TYPE OF FIT	FLAT ROOT SIDE FIT		

SUN GEARS- SUGGESTED MOTOR SHAFT LENGTHS

SUN GEAR	SHAFT TYPE	MIN. (IN.)	MAX. (IN.)
16B	7/8" 13T SPLINE	1.40	1.75
16C	1" 15T SPLINE	1.70	1.95
16D	1" ST. KEYED	1.80	2.10
16E	C/L 2000 BEARINGLESS	N/A	N/A
16F	C/L 4000 BEARINGLESS	N/A	N/A
16H	1 1/4" ST. KEYED	2.05	2.40
16I	1 1/4" 14T SPLINE	2.00	2.32
16M	1" SAE 6B SPLINE	1.95	2.30

THIS DRAWING CONTAINS PROPRIETARY AND CONFIDENTIAL INFORMATION OF HECO GEAR, INC. IN ACCEPTING THIS DRAWING, (CUSTOMER) ACKNOWLEDGES THE VALUE OF THE INTELLECTUAL PROPERTY CONTAINED HEREIN AND AGREES THAT THE INFORMATION IN THIS DRAWING IS THE PROPERTY OF AND PROPRIETARY TO HECO GEAR, INC. AND MAY NOT BE REPRODUCED WITHOUT THE EXPRESS WRITTEN PERMISSION OF HECO GEAR, INC. ALL RIGHTS RESERVED.

©COPYRIGHT 2002, HECO GEAR, INC.

REV	DESCRIPTION	DATE	APPROVED
-	---	--	--
-	---	--	--
-	---	--	--
-	---	--	--
-	---	--	--
-	---	--	--



2330 DEL MONTE STREET
WEST SACRAMENTO, CA 95691
(916)-372-9411 FAX (916)-373-0852

TITLE MODEL 50 ASSEMBLY			
DESCRIPTION HECO MODEL 50 CODE: 50DCF4 4 31			
SIZE D	DRAWN BY: KSC	DWG NO.:	REV --
SCALE: DO NOT SCALE		DATE: 02/08/02	SHEET 1 OF 1